



### **Meinberg Radio Clocks**

Auf der Landwehr 22  
31812 Bad Pyrmont, Germany  
Phone: +49 (5281) 9309-0  
Fax: +49 (5281) 9309-30  
<http://www.meinberg.de>  
[info@meinberg.de](mailto:info@meinberg.de)

## **DU35K: LED Large Display DU35K (three rows, day of week, date, time)**

**LED Large Display DU35K with three rows for day-of-the-week, date and time**

### **Key Features**

- Stand Alone Clock
- 20mA Interface
- 50mm LED Display for Time and Date
- RS232 interface
- Display for external Clock
- DCF77 Receiver (Option)
- Cascadable

## Description

Large display DU35K with good visibility and 50mm height LED characters, working as

- \* radio clock with integrated DCF77 receiver (optional)
- \* free running clock (with or without automatic changeover in daylight saving)
- \* or as externally driven display, via serial timestring (RS232 or current loop)

## Characteristics

|                                   |   |
|-----------------------------------|---|
| <b>Form Factor</b>                | Plastic coated steel sheet case, black (optional: white)  |
| <b>Display</b>                    | LED-Matrix Display (7 dots high) for time and date 50mm character height Without RF signal the clock runs on XTAL with an accuracy of $\pm 1 \cdot 10^{-5}$ , indicated by LED  |
| <b>Interface</b>                  | One serial RS232/20mA interface   |
| <b>Data format of interfaces</b>  | Baudrate: 9600 Baud<br>Dataformat: 7E2<br>1 active/passive 20mA current loop output (selectable)<br>1 active/passive 20mA current loop input (selectable)<br>[1] <a href="#">Output string</a> : 32 ASCII characters with date, time and status information   |
| <b>Physical dimensions</b>        | 323mm x 323mm x 57mm ( width x height x depth)  |
| <b>Electrical connectors</b>      | 1 x 25 pin, 1 x 9 pin DSub female connector<br>BNC antenna connector (only DCF77 variant)<br>power cord receptacle  |
| <b>Backup battery type</b>        | In case of supply voltage failure the on-board RTC keeps the time based on XTAL for more than 100 hours   |
| <b>Power supply</b>               | 85-264VAC (50/60Hz) / 120-375VDC  |
| <b>Ambient temperature</b>        | 0 ... 50°C / 32 ... 122°F   |
| <b>Humidity</b>                   | Max. 85%  |
| <b>Options</b>                    | Variant DU35K/FDM for displaying mains frequency in combination with mains frequency deviation monitor[2] <a href="#">FDM509</a>  |
| <b>RoHS-Status of the product</b> | This product is fully RoHS compliant  |
| <b>WEEE status of the product</b> | This product is handled as a B2B category product. In order to secure a WEEE compliant waste disposal it has to be returned to the manufacturer. Any transportation expenses for returning this product (at its end of life) have to be incurred by the end user, whereas Meinberg will bear the costs for the waste disposal itself. |

### Manual

The english manual is available as a PDF file: [3] [Download \(PDF\)](#)

**Links:**

[1] <http://www.meinberg.de/english/products/./specs/timestr.htm>

[2] <http://www.meinberg.de/english/products/fdm509.htm>

[3] <http://www.meinberg.de/download/docs/manuals/english/du35k.pdf>